

Improved transducer.

5

BACKGROUND OF THE INVENTION

1. Field of the Invention

10

The present invention concerns an improved transducer or, in other words, an element for reproducing and/or recording sound, in particular a loudspeaker or microphone.

15 For clarity's sake, the following description will only deal with transducers for reproducing sound, in other words sound reproducers.

In particular, the invention concerns piezo-electric  
20 reproducers of the type which make use of a vibration membrane onto which is fixed a piezo-ceramic disc.

This membrane is usually fixed to a holder in the shape of a frame or the like, along its perimeter, whereby it is  
25 glued to this holder along its perimeter with a hard or flexible glue.

2. Discussion of the Related Art

30 It is known that by applying an alternating voltage to the piezo-ceramic disc, the material of the piezo-ceramic disc

will start to expand or shrink, and, as the membrane itself cannot expand or shrink, the whole will bend as a function of the voltage variations, as a result of which a sound signal will be generated which is proportional to the  
5 frequency and the amplitude of the applied signal.

In Belgian patents 1,011,085 and 1,011,559 of the applicant are described improvements to the aforesaid type of transducers whereby use is made of a metal membrane and  
10 whereby, in the case of patent BE 1,011,559, an elastic muffling layer made of silicones is provided on this metal membrane, comprising metal particles such as lead or the like.

15 A disadvantage of such a transducer with a muffling layer with metal particles is that these metal particles are very hard to recover from the muffling layer, so that these particles cannot be recycled and, as a consequence, when the transducer is discarded, it will end up on the waste  
20 heap and thus form a burdening for the environment.

In Belgian patent number 1,013,592 of the applicant, additional improvements to the aforesaid type of transducers are described whereby, in this case, a membrane  
25 is applied made of a material muffling sound vibrations, in particular a soft material such a plastic or the like.

Although the reproducers, as described in the aforesaid patents, offer very good results, the invention aims an  
30 improved transducer with unequalled results in the field of

sound quality, which moreover is less harmful to the environment when being discarded.

5

## SUMMARY OF THE INVENTION

To this end, the invention concerns an improved transducer which mainly consists of a membrane onto which is provided  
10 a one-piece or multipart piezo-electric element, wherein the membrane is composed of two or several layers of which at least one layer is made of polymer, elastomer, foamed or filled with synthetic fibers, isotropically mixed or woven fibers made of polymer or elastomer.

15

The membrane preferably consists of a combination of one or several layers made of polymer and one or several layers of metal foil, such as aluminum or brass foil.

20 Thanks to this combination of different layers, the thickness and rigidity of the membrane, depending on the application, can be adjusted in order to obtain a very accurate reproduction of the applied signal coming from a signal generator such as an amplifier, a video recorder, a  
25 mobile phone or the like.

## BRIEF DESCRIPTION OF THE DRAWINGS

30

In order to better explain the characteristics of the invention, the following preferred embodiments of an improved transducer according to the invention are described as an example only without being limitative in  
5 any way, with reference to the accompanying drawings, in which:

figure 1 schematically represents an improved transducer according to the invention;  
10 figure 2 represents an elevation according to arrow F2 in figure 1;  
figure 3 represents the part indicated by F3 in figure 1 to a larger scale;  
figures 4 to 7 represent variants of figure 3;  
15 figures 8 and 9 represent an improved transducer provided in a housing;  
figures 10 to 15 represent variants of figure 2, but to a smaller scale;  
figure 16 represents a variant of figure 1;  
20 figure 17 represents a view according to arrow F17 in figure 16;  
figures 18 and 19 represent other embodiments of an improved transducer provided in a housing.

25

#### DESCRIPTION OF THE PREFERRED EMBODIMENT

As is schematically represented in figures 1 to 3, the  
30 improved transducer according to the invention mainly consists of a holder 1, in this case a rectangular frame

made of plastic or the like; a membrane 2 which is fixed to the holder 1 at its perimeter by means of a flexible glue 3 or the like; a piezo-electric element 4 in the shape of a piezo-ceramic disc which is fixed to the membrane 2, for example by means of gluing, whereby this piezo-electric element 4 is provided with electric conductors 5 for connecting the transducer to a signal generator which is not represented in the figures.

10 The invention is special in that the membrane 2 of the improved transducer is composed of two or several layers, in this case of two layers, a layer 6 made of a metal or a metal alloy and a layer 7 respectively, made of a polymer.

15 The layer 6 is preferably formed of a thin metal foil.

The layer 7 may consist of a foaming polymer, an expanded polymer, a molded polymer or the like, either or not filled with fibers, such as carbon fibers.

20

The piezo-electric element 4 is fixed to one side of the metal layer 6, whereas the layer 7 made of polymer is provided to the opposite side of this layer 6, for example by means of gluing.

25

The working of the improved transducer is based on the principle that when an electric signal is applied to the conductors 5, the membrane 2 will start to vibrate as a function of this signal. This causes an air displacement, as a result of which sound is generated.

30

By applying a membrane 2 with a layered structure, depending on the desired application, the rigidity and thickness of the membrane 2 are adjusted in order to obtain a more accurate reproduction of the applied signal.

5

The membrane 2 can be composed according to the invention of any combination of layers 6 made of metal and layers 7 made of polymer.

10 This is illustrated by way of an example by means of figures 4 to 6, whereby, in these cases, the membrane 2 is respectively formed of:

- 15 - a layer 6 made of metal with two layers 7 made of polymer in the case of figure 4;
- a membrane 2, as in figure 4, with an additional layer 6 made of metal on it in the case of figure 5;
- a membrane 2, as in figure 5, with an additional layer 7 made of polymer on it in the case of figure 6.

20

Also a combination of solely layers 7 made of polymer is possible, as is represented for example by means of figure 7 in which two layers 7 are applied.

25 It is clear that, when several layers 6 made of metal and/or several layers 7 made of polymer are applied, these layers 6-7 do not necessarily have to be made of the same metal or the same polymer.

30 Figure 8 represents a variant of a transducer according to the invention, whereby, in this case, the membrane 2 is not

provided on a frame-shaped holder 1, but is fixed directly, by means of gluing or the like, to a wall 8, for example to a wall 8 of a housing 9 of a loudspeaker, microphone, mobile phone, hearing aid or another audio device.

5

When the wall 8 of a housing 9 is also formed of metal or polymer in this case, said wall 8 may serve as a layer 6 or 7 of the membrane 2 concerned, such that the transducer is in fact integrated in this wall 8 and/or the housing 9.

10

Figure 9 represents a variant whereby the membrane 2 is integrated in a polymer housing 9 and whereby the membrane 2 is formed of a wall 8 of this housing 9 and a layer 6 made of a metal foil glued to the wall 8 and onto which the

15

piezo-electric element 4 is fixed.

An advantage resulting from this integration of the membrane 2 in a wall 8 and/or housing 9 is that the transducer must not be provided behind a perforated wall, which no doubt offers an aesthetic advantage on the one

20

hand and implies less losses and distortions of the emitted sound on the other hand.

In practice it was found that the best results are obtained when the shape of the piezo-electric element 4, in particular the shape of the perimeter of this piezo-electric element 4, is different from the shape of the membrane 2, and in particular when the membrane 2 is preferably not round and does not have a symmetry over 360°

30

in relation to the shape of the piezo-electric element 4.

Figures 10 to 15 represent some possible shapes of improved transducers according to the invention, whereby, in particular in figures 13 to 15, a multipart piezo-electric element 4 is represented which is formed of several,  
5 mutually connected parts 10.

The present invention can be either or not combined with the characteristics of the invention described in the aforesaid patent BE 1,013,592.

10

Thus, for example, as represented in figures 16 and 17, the membrane 2 can be provided with one or several grooves 11 along its perimeter penetrating in one or several layers 6 and/or 7.

15

Further, it is also possible according to patent BE 1,013,592 to fix the membrane 2, as represented in figure 18, in a frame-shaped holder 1 with a U-shaped section or, as in the case of figure 19, on a frame-shaped holder 1  
20 which is fixed to a housing 9 or which is part of it.

The invention is by no means limited to the above-described embodiments given as an example and represented in the accompanying drawings; on the contrary, such an improved  
25 transducer according to the invention can be made in all sorts of shapes and dimensions while still remaining within the scope of the invention.